



National Institute for Occupational Safety and Health  
National Personal Protective Technology Laboratory  
P.O. Box 18070  
Pittsburgh, PA 15236

Procedure No. RCT-ASR-STP-0125A	Revision: 1.1	Date: 12 September 2005
---------------------------------	---------------	-------------------------

DETERMINATION OF GAS TIGHTNESS TEST (ISOAMYL ACETATE) - SELF-CONTAINED BREATHING APPARATUS WITH HOODS OR HELMETS  
STANDARD TESTING PROCEDURE (STP)

1. PURPOSE

This test establishes the procedures for ensuring that the level of protection provided by the gas tightness test requirements on Self-Contained Breathing Apparatus (SCBA) with Hoods or Helmets Respirators submitted for Approval, Extension of Approval, or examined during Certified Product Audits, meet the minimum certification standards set forth in 42 CFR, Part 84, Subpart G, Section 84.63(a)(c)(d), and Subpart H, Section 84.104(a)(b), Volume 60, Number 110, June 8, 1995.

2. GENERAL

This STP describes the Determination of Gas Tightness Test (Isoamyl Acetate) - Self-Contained Breathing Apparatus with Hoods or Helmets test in sufficient detail that a person knowledgeable in the appropriate technical field can select equipment with the necessary resolution, conduct the test, and determine whether or not the product passes the test.

3. EQUIPMENT/MATERIALS

3.1. The list of necessary test equipment and materials follows:



3.1.1. Isoamyl acetate - 99%. Source - Mallinckrodt P/N 2491 or equivalent.

Approvals:	<u>1st</u> Level	<u>2nd</u> Level	<u>3rd</u> Level



3.1.2. 10' x 12', Gas-Tight, Isoamyl acetate chamber or equivalent.



3.1.3. 100 ml graduated cylinder or equivalent.

3.1.4. Six test subjects meeting requirements of the NIOSH Human Subject Review Board (HSRB) approved Protocol. Refer to HSRB-73-DSR-01, "Protocol for the Testing of Respiratory Protective Devices" for the proper consent form and complete details on the use of human test subjects in respirator certification testing.

#### 4. TESTING REQUIREMENTS AND CONDITIONS

- 4.1. Prior to beginning any testing, all measuring equipment to be used must have been calibrated in accordance with the manufacturer's calibration procedure and schedule. At a minimum, all measuring equipment utilized for this testing must have been calibrated within the preceding 12 months using a method traceable to the National Institute of Standards and Technology (NIST).
- 4.2. The compressed gas cylinder must meet all applicable Department of Transportation Requirements for cylinder approval as well as for retesting/requalification.
- 4.3. Normal laboratory safety practices must be observed. This includes all safety precautions described in the current ALOSH Facility Laboratory Safety Manual.
  - 4.3.1. Safety glasses, lab coats, and hard-toe shoes must be worn at all times.

- 4.3.2. Work benches must be maintained free of clutter and non-essential test equipment.
- 4.3.3. When handling any glass laboratory equipment, lab technicians and personnel must wear special gloves which protect against lacerations or punctures.

## 5. PROCEDURE

Note: Reference Section 3 for equipment, model numbers and manufacturers. For calibration purposes use those described in the manufacturer's operation and maintenance manuals.

- 5.1. Close the inside and outside vents, and turn off vacuum. Replace rubber stoppers in side bulkhead fittings.
- 5.2. Measure 87.5 ml. of isoamyl acetate and pour into cloth wick in chamber. Allow the isoamyl acetate to completely evaporate.
- 5.3. When the isoamyl acetate is evaporated, then begin test. Each time the test subject enters or exits the chamber the following procedure must be used:
  - 5.3.1. Subject enters small room.
  - 5.3.2. Outside vent is opened.
  - 5.3.3. Vacuum is turned on for approximately 15 seconds.
  - 5.3.4. Vent is closed.
  - 5.3.6. Subject is then allowed to enter large chamber or exit into the room.
- 5.4. A subject will don the apparatus as per the manufacturer's instructions.
- 5.5. The subject will enter the chamber and perform the following exercises for 1 minute each while wearing the apparatus: nodding and turning head; callisthenic arm movements; deep breathing; and pumping with a tire pump.
- 5.6. Steps 5.4 and 5.5 will be repeated by six different subjects.
- 5.7. No test subject shall smell or taste the test gas, to meet minimum performance requirements. If at any time during the test, the subject detects the banana-like odor of IAA, the test has failed. The subject shall quickly exit from the test chamber and leave the test area to avoid olfactory fatigue.
- 5.8. This procedure will be repeated by at least six different subjects. All subjects' comments will be written on the test data sheet.

Procedure No. RCT-ASR-STP-0125A	Revision: 1.1	Date: 12 September 2005	Page 4 of 7
---------------------------------	---------------	-------------------------	-------------

5.9. Open door vent and inside door, remove rubber stopper in side bulkhead fittings, and exhaust.

5.10. Allow chamber to exhaust for 3-4 hours, replace stoppers and turn off vacuum.

Note: This test should be done on a minimum of two respirators or more if additional testing is required (42 CFR, Part 84, Sections 84.12, 84.30, and 84.60.)

6. PASS/FAIL CRITERIA

6.1. The criterion for passing this test is set forth in 42 CFR, Part 84, Subpart G, Section 84.63(a)(c)(d), and Subpart H, Section 84.104(a)(b), Volume 60, Number 110, June 8, 1995.

6.2. This test establishes the standard procedure for ensuring that:

84.63 Test requirements; general.

(a) Each respirator and respirator component shall when tested by the applicant and by the Institute, meet the applicable requirements set forth in subparts H through L of this part.

(c) In addition to the minimum requirements set forth in subparts H through L of this part, the Institute reserves the right to require, as a further condition of approval, any additional requirements deemed necessary to establish the quality, effectiveness, and safety of any respirator used as protection against hazardous atmospheres.

(d) Where it is determined after receipt of an application that additional requirements will be required for approval, the Institute will notify the applicant in writing of these additional requirements, and necessary examinations, inspections, or tests, stating generally the reasons for such requirements, examinations, inspections, or tests.

84.104 Gas Tightness Test; minimum requirements.

(a) Each apparatus will be tested for tightness by persons wearing it in an atmosphere of 500 ppm isoamyl acetate vapor.

(b) Six persons will each wear the apparatus in the test concentrations specified in paragraph (a) of this section for two minutes and none shall detect the odor or taste of the test vapor.

6.3. NIOSH has increased the severity of the gas tightness test for approval of all Self Contained Breathing Apparatus (SCBA), over that specified in subpart 84.104(a)(b), to assure safe operation of such apparatus, particularly those incorporating hoods and helmets. The test time specified in subpart 84.104(a)(b) is increased to 4 minutes or until the service life is complete and the following exercises are performed for 1 minute each while wearing the apparatus:

- 6.3.1 Nodding and turning head; callisthenic arm movements; deep breathing; and pumping with a tire pump.

## 7. RECORDS\TEST SHEETS

- 7.1. All test data will be recorded on the GAS TIGHTNESS TEST - ISOAMYL ACETATE, SELF-CONTAINED BREATHING APPARATUS WITH HOODS OR HELMETS test data sheet.
- 7.2. All videotapes and photographs of the actual test being performed, or of the tested equipment shall be maintained in the task file as part of the permanent record.
- 7.3. All equipment failing any portion of this test will be handled as follows:
  - 7.3.1. If the failure occurs on a new certification application, or extension of approval application, send a test report to the RCT Leader and prepare the hardware for return to the manufacturer.
  - 7.3.2. If the failure occurs on hardware examined under an Off-the-Shelf Audit the hardware will be examined by a technician and the RCT Leader for cause. All equipment failing any portion of this test may be sent to the manufacturer for examination and then returned to NIOSH. However, the hardware tested shall be held at the testing laboratory until authorized for release by the RCT Leader, or his designee, following the standard operating procedures outlined in Procedure for Scheduling, and Processing Post-Certification Product Audits, RB-SOP-0005-00.

**GAS TIGHTNESS TEST - ISOAMYL ACETATE,  
SELF-CONTAINED BREATHING APPARATUS  
WITH HOODS OR HELMETS**

Project No. : \_\_\_\_\_ Date: \_\_\_\_\_

Company : \_\_\_\_\_

Respirator Type: \_\_\_\_\_

Reference: 42 CFR, Part 84, Subpart H, 84.104(a)(b).

Requirement: The completely assembled respirator will be worn in 500ppm. IAA vapor and not one of the test subjects shall detect any odor of the test gas or vapor in the air breathed during any such test, and the wearer shall not be subjected to any undue discomfort or encumbrance because of the fit, air delivery, or other features of the respirator during the testing period. The following regimen is followed in the test chamber:

- one minute nodding and turning head, walking, and bending:.
- one minute - pumping air with a tire pump into a 28 liter container.

Test Subject #1 Comments:  
\_\_\_\_\_  
\_\_\_\_\_

Test Subject #2 Comments:  
\_\_\_\_\_  
\_\_\_\_\_

Test Subject #3 Comments:  
\_\_\_\_\_  
\_\_\_\_\_

Test Subject #4 Comments:  
\_\_\_\_\_  
\_\_\_\_\_

Test Subject #5 Comments:  
\_\_\_\_\_  
\_\_\_\_\_

Test Subject #6 Comments:  
\_\_\_\_\_  
\_\_\_\_\_

Test Engineer: \_\_\_\_\_ Pass: \_\_\_\_\_ Fail: \_\_\_\_\_

### Revision History

<b>Revision</b>	<b>Date</b>	<b>Reason for Revision</b>
	February 1996	NIOSH has reduced the IDLH for isoamyl acetate in the Pocket Guide to Chemical Hazards from 3000 ppm to 1000 ppm. This resulted in the NIOSH STP being run at the IDLH concentration contrary to good work practices, and OSHA standards which stipulate the “concentrations during the test shall not exceed an OSHA permissible exposure limit, the ACGIH threshold limit values, or any known recommended exposure limit, when there is no OSHA PEL or ACGIH TLV, and not create a health or physical hazard for the test subject or operator.” In the face of these facts, the test concentration was reduced to the OSHA PEL and NIOSH REL of 500 ppm with commitment to revisit the appropriateness of the test, and of isoamyl acetate as the test agent of choice in future regulation change modules.
1.0	31 January 2000	Historic document
1.1	12 September 2005	Update header and format to reflect lab move from Morgantown, WV No changes to method