

National Institute for Occupational Safety and Health National Personal Protective Technology Laboratory P.O. Box 18070 Pittsburgh, PA 15236

Procedure No. RCT-ASR-STP-0144

Revision: 1.1

Date: 12 September 2005

DETERMINATION OF CONTINUOUS GAS FLOW ON CONSTANT FLOW, CLOSED-CIRCUIT, SELF-CONTAINED BREATHING APPARATUS STANDARD TESTING PROCEDURE (STP)

1. PURPOSE

This test establishes the procedures for ensuring that the level of protection provided by the gas flow requirements on Constant Flow, Closed-Circuit, Self-Contained Breathing Apparatus (SCBA) submitted for Approval, Extension of Approval, or examined during Certified Product Audits, meet the minimum certification standards set forth in 42 CFR, Part 84, Subpart G, Section 84.63(a)(c)(d), and Subpart H, Section 84.94(a); Volume 60, Number 110, June 8, 1995.

2. GENERAL

This STP describes the Determination of Continuous Gas Flow on Constant Flow, Closed-Circuit, Self-Contained Breathing Apparatus test in sufficient detail that a person knowledgeable in the appropriate technical field can select equipment with the necessary resolution, conduct the test, and determine whether or not the product passes the test.

3. <u>EQUIPMENT/MATERIALS</u>

3.1. The list of necessary test equipment and materials follows:



3.1.1. Electric Timer, calibrated to hundredths of a minute (Precision Scientific Company) or equivalent.

Approvals:	1 <u>st</u> Level	2 <u>nd</u> Level	3 <u>rd</u> Level



3.1.2. Dry test - Gas meter, (Singer-American Meter Division - Model DTM-200A) or equivalent.



3.1.3. Wet Test - Gas Meter (Singer-American Meter Company - Model AL17-1) or equivalent.

4. TESTING REQUIREMENTS AND CONDITIONS

- 4.1. Prior to beginning any testing, all measuring equipment to be used must have been calibrated in accordance with the manufacturer's calibration procedure and schedule. At a minimum, all measuring equipment utilized for this testing must have been calibrated within the preceding 12 months using a method traceable to the National Institute of Standards and Technology (NIST).
- 4.2. The compressed gas cylinder must meet all applicable Department of Transportation requirements for cylinder approval as well as for retesting/requalification.
- 4.3. Normal laboratory safety practices must be observed. This includes all safety precautions described in the current ALOSH Facility Laboratory Safety Manual.
 - 4.3.1. Safety glasses, lab coats, and hard-toe shoes must be worn at all times.
 - 4.3.2. Work benches must be maintained free of clutter and non-essential test equipment.
 - 4.3.3. When handling any glass laboratory equipment, lab technicians and personnel must wear special gloves which protect against lacerations or punctures.

5. PROCEDURE

Note: Reference Section 3 for equipment, model numbers and manufacturers. For calibration

purposes use those described in the manufacturer's operation and maintenance manuals.

- 5.1. The regulator or constant flow outlet is connected to a calibrated wet test meter (traceable to NIST using Dry Test Gas Meter).
- 5.2. Flow readings are recorded initially and every 10 minutes for the rated service time of the unit. The last 10 minutes are monitored every other minute.
- 5.3. Data Analysis

Record flow readings directly from the wet test gas meter.

Note: This test should be done on a minimum of two respirators, or more if additional testing is required (42 CFR, Part 84, Sections 84.12, 84.30, and 84.60).

6. PASS\FAIL CRITERIA

- 6.1. The criterion for passing this test is set forth in 42 CFR, Part 84, Subpart G, Section 84.63(a)(c)(d), and Subpart H, Section 84.94(a); Volume 60, Number 110, June 8, 1995.
- 6.2. This test establishes the standard procedure for ensuring that:
 - 84.63 Test requirements; general.
 - (a) Each respirator and respirator component shall when tested by the applicant and by the Institute, meet the applicable requirements set forth in subparts H through L of this part.
 - (c) In addition to the minimum requirements set forth in subparts H through L of this part, the Institute reserves the right to require, as a further condition of approval, any additional requirements deemed necessary to establish the quality, effectiveness, and safety of any respirator used as protection against hazardous atmospheres.
 - (d) Where it is determined after receipt of an application that additional requirements will be required for approval, the Institute will notify the applicant in writing of these additional requirements, and necessary examinations, inspections, or tests, stating generally the reasons for such requirements, examinations, inspections, or tests.
 - 84.94 Gas flow test; closed-circuit apparatus.
 - (a) Where oxygen is supplied by a constant-flow device only, the rate of flow shall be at least 3 liters per minute for the entire rated service time of the apparatus.

7. RECORDS\TEST SHEETS

7.1. All test data will be recorded on the GAS FLOW TEST, CONSTANT FLOW, CLOSED-CIRCUIT, SELF-CONTAINED BREATHING APPARATUS test data sheet.

Procedure No. RCT-ASR-STP-0144	Revision: 1.1	Date: 12 September 2005	Page 4 of 13
--------------------------------	---------------	-------------------------	--------------

- 7.2. All videotapes and photographs of the actual test being performed, or of the test equipment shall be maintained in the task file as part of the permanent record.
- 7.3. All equipment failing any portion of this test will be handled as follows;
 - 7.3.1. If the failure occurs on a new certification application, or extension of approval application, send a test report to the RCT Leader and prepare the hardware for return to the manufacturer.
 - 7.3.2. If the failure occurs on hardware examined under an Off-the-Shelf Audit the hardware will be examined by a technician and the RCT Leader for cause. All equipment failing any portion of this test may be sent to the manufacturer for examination and then returned to NIOSH. However, the hardware tested shall be held at the testing laboratory until authorized for release by the RCT Leader, or his designee, following the standard operating procedures outlined in Procedure for Scheduling, and Processing Post-Certification Product Audits, RB-SOP-0005-00.

Procedure No. RCT-ASR-STP-0144	Revision: 1.1	Date: 12 September 2005	Page 5 of 13
--------------------------------	---------------	-------------------------	--------------

GAS FLOW TEST, CONSTANT FLOW, CLOSED-CIRCUIT, SELF-CONTAINED BREATHING APPARATUS

Project No.	:	Date:
Company	:	
Respirator Type	e:	
Reference:	42 CFR 84, Subpart H, Section 84.94(a).	
Requirement:	Where oxygen is supplied by a constant-flow device only least 3 liters per minute for the entire rated service time of	

Results:

<u>Unit #1</u>	Time/Min.	Flow/LPM	<u>Unit #2</u>	Time/Min.	Flow/LPM
	0-1			0-1	
	1-2			1-2	
	2-3			2-3	
	3-4			3-4	
	4-5			4-5	
	5-6			5-6	
	6-7			6-7	
	7-8			7-8	
	8-9			8-9	
	9-10			9-10	
	10-11			10-11	
	11-12			11-12	
	12-13			12-13	
	13-14			13-14	
	14-15			14-15	
	15-16			15-16	
	16-17			16-17	
	17-18			17-18	
	18-19			18-19	
	19-20			19-20	
	20-21			20-21	
	21-22			21-22	
	22-23			22-23	
	23-24			23-24	
	24-25			24-25	
	25-26			25-26	
	26-27			26-27	
	27-28			27-28	

Procedure No. RCT-ASR-STP-0144 Revision: 1.1 Date: 12 September 2005 Page 6 of 13 28-29 29-30 29-30 29-30 30-31 30-31 30-31 31-32 31-32 31-32 32-33 32-33 32-33 33-34 33-34 33-34 34-35 34-35 35-36 36-37 36-37 36-37 37-38 37-38 37-38 38-39 38-39 39-40 40-41 40-41 40-41 41-42 41-42 41-42 42-43 42-43 42-43 43-44 43-44 43-44 44-45 44-45 44-45 45-46 45-46 45-46	
29-30 29-30 30-31 30-31 31-32 31-32 32-33 32-33 33-34 33-34 34-35 34-35 35-36 35-36 36-37 36-37 37-38 37-38 38-39 38-39 39-40 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
29-30 29-30 30-31 30-31 31-32 31-32 32-33 32-33 33-34 33-34 34-35 34-35 35-36 35-36 36-37 36-37 37-38 37-38 38-39 38-39 39-40 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
30-31 30-31 31-32 31-32 32-33 32-33 33-34 33-34 34-35 34-35 35-36 35-36 36-37 36-37 37-38 37-38 38-39 38-39 39-40 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
31-32 31-32 32-33 32-33 33-34 33-34 34-35 34-35 35-36 35-36 36-37 36-37 37-38 37-38 38-39 38-39 39-40 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
32-33 32-33 33-34 33-34 34-35 34-35 35-36 35-36 36-37 36-37 37-38 37-38 38-39 38-39 39-40 40-41 40-41 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
33-34 33-34 34-35 34-35 35-36 35-36 36-37 36-37 37-38 37-38 38-39 38-39 39-40 40-41 40-41 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
34-35 34-35 35-36 35-36 36-37 36-37 37-38 37-38 38-39 38-39 39-40 40-41 40-41 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
35-36 35-36 36-37 36-37 37-38 37-38 38-39 38-39 39-40 40-41 40-41 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
36-37 36-37 37-38 37-38 38-39 38-39 39-40 40-41 40-41 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
37-38 37-38 38-39 38-39 39-40 39-40 40-41 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
38-39 38-39 39-40 39-40 40-41 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
39-40 39-40 40-41 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
40-41 40-41 41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
41-42 41-42 42-43 42-43 43-44 43-44 44-45 44-45	
42-43 42-43 43-44 43-44 44-45 44-45	
43-44 44-45 43-44 44-45	
44-45 44-45	
45-46	
46-47 46-47	
47-48 47-48	
48-49	
49-50 49-50	
50-51 50-51	
51-52 51-52	
52-53 52-53	
53-54	
54-55	
55-56 55-56	
56-57 56-57	
57-58	
58-59 58-59	
59-60 59-60	
60-61 60-61	
61-62	
62-63	
63-64 63-64	
64-65 64-65	
65-66	
66-67 66-67	
67-68 67-68	
68-69 68-69	
69-70	
71-72 71-72	
72-73 72-74	
73-74 73-74	
74-75 74-75	
75-76 75-76	

Procedure No. RCT-ASR-STP-0144	Revision: 1.1	Date: 12 September 2005	Page 7 of 13
	•		•
76-77		76-77	
77-78		77-78	
78-79		78-79	
79-80		79-80	
80-81		80-81	
81-82		81-82	
82-83		82-83	
83-84		83-84	
84-85		84-85	
85-86		85-86	
86-87		86-87	
87-88		87-88	
88-89	·	88-89	
89-90		89-90	
90-91		90-91	-
91-92		91-92	-
92-93		92-93	
93-94		93-94	
94-95	-	94-95	-
95-96	-	95-96	-
96-97	-	96-97	-
97-98		97-98	
98-99	·	98-99	
99-100	·	99-100	
100-101	-	100-101	-
101-102		101-102	
102-103	·	102-103	
103-104	-	103-104	
104-105		104-105	
105-106	·	105-106	
106-107	·	106-107	
107-108		107-108	
108-109		108-109	
109-110		109-110	
110-111		110-111	
111-112		111-112	
112-113		112-113	
113-114		113-114	
113-114		114-115	
115-116	·	115-116	
116-117		116-117	
110-117		117-118	
118-119		118-119	
119-119		119-119	
120-121		120-121	
120-121 121-122		120-121 121-122	
121-122		121-122	
122-123		122-123	
123-124		123-124	

			I
Procedure No. RCT-ASR-STP-0144	Revision: 1.1	Date: 12 September 2005	Page 8 of 13
124-125		124-125	
125-126		125-126	
126-127		126-127	
127-128		127-128	
128-129		128-129	
129-130		129-130	
130-131		130-131	- <u></u> -
131-132		131-132	
132-133		132-133	
133-134		133-134	
134-135		134-135	
135-136		135-136	
136-137		136-137	
137-138		137-138	
138-139		138-139	
139-140		139-140	
140-141		140-141	
141-142		141-142	
142-143		142-143	
143-144		143-144	
144-145		144-145	
145-146		145-146	
146-147		146-147	
147-148		147-148	
148-149		148-149	
149-150		149-150	
150-151		150-151	
151-152		151-152	
151-132		151-152	
153-154		153-154	
154-155		154-155 155-156	
155-156		155-156	
156-157		156-157	
157-158		157-158	
158-159		158-159	
159-160		159-160	
160-161		160-161	
161-162		161-162	
162-163		162-163	
163-164		163-164	
164-165		164-165	
165-166		165-166	
166-167		166-167	
167-168		167-168	
168-169		168-169	
169-170		169-170	
170-171		170-171	
171-172		171-172	

	<u> </u>	Tp. 40 7	D 0 215
Procedure No. RCT-ASR-STP-0144	Revision: 1.1	Date: 12 September 2005	Page 9 of 13
172-173		172-173	
173-174		173-174	
174-175		174-175	
175-176		175-176	
176-177		176-177	
177-178		177-178	
178-179		178-179	
179-180		179-180	
180-181		180-181	
181-182		181-182	
182-183		182-183	
183-184		183-184	
184-185		184-185	
185-186		185-186	
186-187		186-187	
187-188		187-188	
188-189		188-189	-
189-190		189-190	
190-191		190-191	
190-191		191-192	-
191-192		192-193	-
193-194		193-194	
194-195		194-195	
195-196		195-196	
196-197		196-197	
197-198	-	197-198	
198-199	-	198-199	-
199-200		199-200	
200-201		200-201	
201-202		201-202	
202-203		202-203	
203-204		203-204	
204-205		204-205	
205-206		205-206	
206-207		206-207	
207-208		207-208	
208-209		208-209	
209-210		209-210	
210-211		210-211	
211-212		211-212	
212-213		212-213	
213-214		213-214	
214-215		214-215	
215-216		215-216	
216-217		216-217	
217-218		217-218	
218-219		218-219	
219-220		219-220	
217-220		217-220	

Procedure No. RCT-ASR-STP-0144	Revision: 1.1	Date: 12 September 2005	Page 10 of 13
220-221		220-221	
220-221		221-222	
222-223		222-223	
223-224		223-224	
224-225		224-225	
225-226		225-226	
226-227		226-227	
227-228		227-228	
228-229		228-229	
229-230		229-230	
230-231		230-231	
231-232		231-232	
232-233		232-233	
233-234		233-234	
234-235		234-235	
235-236		235-236	
236-237		236-237	
237-238		237-238	
238-239		238-239	
239-240		239-240	
Comments:			
Test Engineer:		PASS FAII	

Procedure No. RCT-ASR-STP-0144

Revision: 1.1


Date: 12 September 2005

Page 11 of 13



Revision: 1.1





Procedure No. RCT-ASR-STP-0144	Revision: 1.1	Date: 12 September 2005	Page 13 of 13
110ccdule No. Re1-ASR-S11-0144	1C V131011. 1.1	Date. 12 September 2005	1 age 13 01 13

Revision History

Revision	Date	Reason for Revision
1.0	24 May 2001	Historic document
1.1	12 September 2005	Update header and format to reflect lab move from Morgantown, WV No changes to method